

# (1) EU-TYPE EXAMINATION CERTIFICATE



- (2) Equipment and Protective Systems intended for use in Potentially Explosive Atmosphere - **Directive 2014/34/EU**
- (3) EU-Type Examination Certificate Number

## TÜV 17 ATEX 8119 X

Issue: 00

- (4) Equipment: **C5000 Power Supply**
- (5) Manufacturer: **Compac Industries Ltd**
- (6) Address: **52 Walls Road, Penrose Auckland  
New Zealand**
- (7) This product and any acceptable variation thereto are specified in the schedule to this certificate and the documents therein referred to.
- (8) The TÜV Rheinland Zertifizierungsstelle für Explosionsschutz of TÜV Rheinland Industrie Service GmbH, Notified Body No. 0035 in accordance with Article 21 of the Council Directive 2014/34/EU of 26<sup>th</sup> February 2014, certifies this product which has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of equipment and protective systems intended for use in potentially explosive atmosphere, given in Annex II to the Directive.  
  
The examination and test results are recorded in the confidential report 557/Ex8119.00/17
- (9) Compliance with the Essential Health and Safety Requirements, with the exception of those listed in the schedule of this certificate, has been assessed by reference to:  
  
**EN 60079-0:2012/A11:2013      EN 60079-1:2014      EN 60079-11:2012**
- (10) If the sign "X" is placed after the certificate number, it indicates that the equipment is subject to special conditions for safe use specified in the schedule to this certificate.
- (11) This EU-Type Examination Certificate relates only to the design and specification for construction of the equipment or protective system. It does not cover the process for actual manufacture or supply of the equipment or protective system, for which further requirements of the directive are applicable.
- (12) The marking of the equipment shall include the following:



**II 2 (2) G**

**Ex db [ib] IIA T4**

**(-40°C ≤ Ta ≤ +55°C or +65°C)**

TÜV Rheinland Zertifizierungsstelle für Explosionsschutz

Cologne, 2017-11-09

Dipl.-Ing. Klauspeter Graffi

This EU-Type Examination Certificate without signature and stamp shall not be valid.  
This EU-Type Examination Certificate may be circulated only without alteration. Extracts or alterations are subject to approval by the TÜV Rheinland Industrie Service GmbH TÜV Rheinland Group Am Grauen Stein 51105 Köln  
Tel. +49 (0) 221 806-0 Fax. + 49 (0) 221 806 114

(13) Annex

(14) **EU Type Examination Certificate**  
**TÜV 17 ATEX 8119 X** Issue: 00

(15) Description of equipment

15.1 Equipment and type:

C5000 Power Supply

15.2 Description / Details of Change

General product information

The “C5000 Power supply” consists of a flameproof box enclosing several printed circuit board assemblies. The Ex protection code for the complete power supply includes db and ib for use in Zone 1 areas.

The equipment includes:

- The flameproof box PDM1442
- The flameproof box lid PDM1443
- The flameproof box cable gland PDM1444
- The flameproof box blanking plugs SW050
- The Processor Board (non-IS) CI500
- The Communication board (non-IS) CI501
- The Terminal board CI504
- The power supply board CI505

The mains terminal board (CI504), the processor board (CI500), the Communication board (CI501), and part of the power supply boards (CI505) are on the non-intrinsically safe side of the electronics, and the outputs from the power supply board (CI505) are intrinsically safe and have been considered in this certificate.

The flameproof box and its accessories provides the Ex d protection. The processor and communication boards do not help provide any protection but must be included in the power supply and need to be considered when calculating the maximum temperature inside the box.

This EU Type Examination Certificate without signature and official stamp shall not be valid.  
This certificate may be circulated without alteration. Extracts or alterations are subject to approval by:  
Zertifizierungsstelle of TÜV Rheinland Industrie Service GmbH

The mains supply is 110-240Vac 50/60Hz 2A (for the models fitted without motor triacs) or 15A (for the models fitted with motor triacs).

As far as the intrinsic safety is concerned the mains fuses (F2, F3) are on the terminal board (CI504). These are the only two components on the terminal board that are required for the intrinsic safety of the output. The fuses are placed on the top side of the PCB and are protected with plastic covers. The tracks after the fuses are on the bottom side of the PCB so cannot be compromised by shorting out to the wiring on the top.

The Power Supply board CI505 is the “associated apparatus” that bridges between the non-intrinsically safe parts and the intrinsically safe outputs. This actually consists of 3 printed circuit boards piggy backed on top of one another. These boards are fitted under the processor and terminal board. This board provides a non-IS 12V 1A. It also provides intrinsically safe 9V supply output, a 5V supply output, and a RS485 connection brought out on a cable through a gland, with a plug with 8 pins.

Type code:

C5000 Power Supply 110-240Vac 50/60Hz 15A (or 2A) IP66

#### Technical Data

Mains input nominal voltage range of 110-240Vac

Tamb -40°C ≤ Ta ≤ +55°C or +65°C

(16) Test-Report No. 557 / Ex 8119.00/17

This EU Type Examination Certificate without signature and official stamp shall not be valid.  
This certificate may be circulated without alteration. Extracts or alterations are subject to approval by:  
Zertifizierungsstelle of TÜV Rheinland Industrie Service GmbH

(17) Special Conditions for safe use

1. The Um of 250Vac is applicable on the non-intrinsically safe connections, with a nominal voltage range of 110-240Vac.

Input output parameters that must be taken into account during interconnection with other intrinsically safe equipment:

<b>C5000 Power Supply I.S. Cable connections:</b>	
<b>5V &amp; RS485</b>	<b>Pins 1, 2, &amp; 6 w.r.t. Pins 3, 4, 5, &amp; 7</b>
Uo	5.2V
Io	192mA
Po	1W
Co	800uF
Lo	2.5mH
<b>9V Output</b>	<b>Pin 8 w.r.t. Pins 3, 4, 5, &amp; 7</b>
Uo	9.6V
Io	960mA
Po	9.2W
Co	15uF
Lo	27uH


2. The intrinsically safe output circuits are bonded to the metallic enclosure, and this must be taken into account when interconnecting in the system.
3. Some flamepaths are different from the standard and must be considered during maintenance / repair using the information supplied by the manufacturer.


(18) Basic Safety and Health Requirements

Covered by afore mentioned standard

TÜV Rheinland Zertifizierungsstelle für Explosionsschutz

Cologne, 2017-11-09

  
 Dipl.-Ing. Klauspeter Graffi



This EU Type Examination Certificate without signature and official stamp shall not be valid.  
 This certificate may be circulated without alteration. Extracts or alterations are subject to approval by:  
 Zertifizierungsstelle of TÜV Rheinland Industrie Service GmbH